

TITLE OF THE INVENTION

COOLING UNIT FOR COOLING HEAT GENERATING COMPONENT AND
ELECTRONIC APPARATUS CONTAINING COOLING UNIT

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the
benefit of priority from Japanese Patent Application
No. 2001-055207, filed February 28, 2001.

BACKGROUND OF THE INVENTION

1. Field of the Invention

10 This invention relates to a cooling unit for
improving the radiation efficiency of a heat generating
component, such as a semiconductor package and an
electric apparatus, such as a portable computer
provided with such a cooling unit.

15 2. Description of the Related Art

Notebook-type portable computers, PDAs (personal
digital assistants) and other portable electronic
apparatuses typically comprise a semiconductor package
for processing multimedia information in the form of
20 characters, sounds, and images. These days, such
semiconductor packages consume more and more energy
as their information processing rates are increased,
and as they are made to provide more multi-
functionally. As a result, they generate
25 proportionally more heat than ever.

Under these circumstances, it is necessary to
improve the radiation efficiency of the semiconductor

5

10

20

25

10

20

2

portion. Thus, the heat transmission path connecting the IC chip and the heat receiving portion shows a small cross section, and hence heat has to be moved at a very high rate per unit area of the thermally connecting zone. Then, the IC chip and the heat receiving portion show a large temperature difference, and heat cannot be transmitted efficiently from the IC chip to the heat sink.

BRIEF SUMMARY OF THE INVENTION

Therefore, it is an object of the present invention to provide a cooling unit that can effectively absorb the dimensional variances of the zone thermally connecting the heat generating component that may typically be an IC chip and the heat sink, and efficiently transmit heat from the heat generating component to the heat sink to improve the radiation efficiency of the heat generating component.

Another object of the present invention is to provide an electronic apparatus containing such a cooling unit.

Additional objects and advantages of the invention will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out herein after.

BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate embodiments of the invention, and together with the general description given above and the detailed description of the embodiments given below, serve to explain the principles of the invention.

FIG. 1 is an exploded schematic perspective view of a first embodiment of the invention, illustrating a positional relationship of a portable computer and a cooling unit thereof;

FIG. 2 is a schematic cross-sectional view of a portable computer, illustrating a positional relationship of a portable computer and a cooling unit of the embodiment;

FIG. 3 is a schematic cross-sectional view of a portable computer, illustrating a positional relationship of a semiconductor package and a cooling unit of the embodiment;

FIG. 4 is a schematic cross-sectional view of a portable computer, illustrating a housing and a cooling unit housed in the housing of the embodiment;

FIG. 5 is a schematic perspective view of a cooling unit of the embodiment;

FIG. 6 is a schematic perspective view of the embodiment, illustrating a positional relationship of a semiconductor package and a heat diffusing member

thereof;

FIG. 7 is a schematic perspective view of a heat diffusing member of the embodiment;

FIG. 8 is a schematic cross-sectional view of the embodiment, illustrating a positional relationship of a BGA-type semiconductor package, a heat diffusing member and a heat sink thereof;

FIG. 9 is a schematic cross-sectional view of the embodiment, illustrating a BGA-type semiconductor package thermally connected to a heat sink by way of a heat diffusing member thereof;

FIG. 10 is a schematic cross-sectional view taken along line F10-F10 in FIG. 9;

FIG. 11A is a schematic cross-sectional view taken along line F11A-F11A in FIG. 9;

FIG. 11B is a schematic cross-sectional view taken along line F11B-F11B in FIG. 9;

FIG. 12 is an exploded perspective view of a part of a portable computer, illustrating a positional relationship of a bottom wall of a housing, a cover, a thermally conductive sheet and a heat sink of the embodiment;

FIG. 13 is a perspective view of a part of a portable computer, illustrating a cover fitted to a bottom wall of a housing of the embodiment;

FIG. 14A is a schematic cross-sectional view of a second embodiment of the invention, illustrating

5

10

15

20

25

FIGS. 1 and 2 show a portable computer 1 as an electronic apparatus and a cooling apparatus 2 adapted to cool the portable computer 1.

5 The portable computer 1 comprises a computer main
body 3 and a display unit 4 held by the computer main
body 3. The computer main body 3 has a flat housing 5.
The housing 5 comprises a bottom wall 5a, a top wall
5b, a front wall 5c, a pair of side walls 5d, and
10 a rear wall 5e. A palm rest 6 and a keyboard fitting
section 7 are arranged on the top wall 5b of the
housing 5. The palm rest 6 is located on the front
half of the top wall 5b of the housing 5, whereas the
15 keyboard fitting section 7 is found behind the palm
rest 6 and a keyboard 8 is arranged in the keyboard
fitting section 7.

20 The display unit 4 has a display housing 10 and
a liquid crystal display panel 11. The liquid crystal
display panel 11 is housed in the display housing 10
and exposed to the outside through the front opening 12
of the display housing 10.

25 The display housing 10 is linked at an end thereof
to the rear end of the housing 5 by way of a hinge
device (not shown). Thus, the display unit 4 can
rotate between a closed position where it completely
covers the palm rest 6 and the keyboard 8 and an open
position where it stands upright to expose the palm
rest 6, the keyboard 8, and the liquid crystal display
panel 11.

As shown in FIGS. 2 and 3, the housing 5 contains
therein a circuit substrate 13. The circuit substrate

13 has a mount surface 13a that faces the bottom wall
5a of the housing 5. A BGA-type semiconductor package
15 is mounted on the mount surface 13a as an electronic
component. The semiconductor package 15 contains
5 a microprocessor that is the core of the portable
computer 1.

As shown in FIGS. 6 and 8, the semiconductor
package 15 comprises a base substrate 16 and an IC chip
17 that is a heat generating component. The base
10 substrate 16 has a rectangular profile having four
corners 18 at the outer periphery thereof. The length
of each side of the base substrate 16 is about 30 mm.
The IC chip 17 processes multimedia information
including characters, sounds, and images at high speeds
15 so that it generates heat at an enhanced rate during
its operation, and hence needs to be cooled in order to
operate stably.

The IC chip 17 has a rectangular profile and is
smaller than the base substrate 16. Each side of the
20 IC chip 17 is about 10 mm. The IC chip 17 is soldered
to the center of one of the opposite surfaces, or
surface 16a, of the base substrate 16. The IC chip 17
has a flat radiation surface 19 located remotely from
the base substrate 16. The radiation surface 19 is
25 slightly projected from the surface 16a of the base
substrate 16.

A number of solder balls 20 are arranged in

the form of a grid on the other surface 16b of the base substrate 16. The solder balls 20 are bonded to the mount surface 13a of the circuit substrate 13. Thus, the semiconductor package 15 is fitted to the circuit substrate 13 with the IC chip 17 facing downward.

As shown in FIGS. 2 through 4, the housing 5 also contains a cooling unit 23 for cooling the semiconductor package 15. The cooling unit 23 comprises a heat sink 24 and an electrically powered fan unit 25.

The heat sink 24 is made of a metal material such as aluminum alloy that is thermally highly conductive. The heat sink 24 has a heat receiving portion 26 and a heat exchanging portion 27. The heat receiving portion 26 has a flat rectangular profile and its surface area is larger than that of the semiconductor package 15. The heat receiving portion 26 is arranged vis-à-vis the semiconductor package 15 between the bottom wall 5a of the housing 5 and the circuit substrate 13.

As shown in FIGS. 4 and 5, the heat receiving portion 26 of the heat sink 24 has four substrate support sections 28a through 28d. The substrate support sections 28a through 28d project respectively from the four corners of the heat receiving portion 26 toward the circuit substrate 13. The circuit substrate 13 is rigidly secured to the free ends of the substrate

support sections 28a through 28d by means of respective screws 29. The circuit substrate 13 is provided with grounding pads (not shown) arranged respectively at the positions contacting the substrate support sections 28a through 28d. Thus, the heat sink 24 is grounded by way of the substrate support sections 28a through 28d and the grounding pads located at the respective positions of the circuit substrate 13 contacting them.

Of the four substrate support sections 28a through 28d, the paired sections 28a, 28c that are arranged on diagonal Z of the heat receiving portion 26 are respectively laid on a pair of boss sections 30a, 30b projecting from the bottom wall 5a of the housing 5. Each of the two screws 29 rigidly securing the circuit substrate 13 is driven respectively through the substrate support sections 28a, 28c into the boss sections 30a, 30b. Thus, the heat receiving portion 26 of the heat sink 24 is directly and rigidly secured to the bottom wall 5a of the housing 5 at two positions on the diagonal Z.

As shown in FIGS. 3 through 5, the heat exchanging portion 27 of the heat sink 24 is integral with the heat receiving portion 26 and thermally connected to the latter. The heat exchanging portion 27 is located between the left lateral wall 5d of the housing 5 as viewed from the front side of the housing 5 and the semiconductor package 15. The heat exchanging

portion 27 has a support wall 31 extending upward from the outer periphery thereof. A metal ceiling plate 32 is rigidly secured to the upper end of the support wall 31. Thus, the ceiling plate 32 is combined with the heat exchanging portion 27 and the support wall 31 to form a cooling air path 33. The cooling air path 33 communicates at the downstream end thereof with a cooling air outlet port 34 that is open at the left lateral wall 5d of the housing 5.

As shown in FIGS. 2 and 4, the fan unit 25 is arranged immediately in front of the heat sink 24. The fan unit 25 comprises a fan casing 36 and a centrifugal type impeller 37.

The fan casing 36 has a first suction port 38, second suction port 39 and a discharge port 40 and is integral with the heat sink 24. The first suction port 38 is located vis-à-vis a number of first air inlet ports 41 open at the bottom wall 5a of the housing 5. The second suction port 39 is located vis-à-vis a number of second air inlet ports 42 open at the palm rest 6. The discharge port 40 is open toward the heat sink 24 and a part thereof faces the upstream end of the cooling air path 33.

The impeller 37 is supported by the fan casing 36 by way of a flat motor 43. The flat motor 43 is electrically connected to the circuit substrate 13. The flat motor 43 is driven to revolve according to

a signal fed from the circuit substrate 13 when the temperature of the semiconductor package 15 reaches a predetermined level.

As the impeller 37 is driven to rotate by the flat motor 43, air is taken in from the inside of the fan casing 36 through the first and second suction ports 38, 39. The air is then discharged from the outer periphery of the impeller 37 as cooling air. Then, the cooling air is sent to the cooling air path 33 and an area surrounding the semiconductor package 15 by way of the discharge port 40.

As shown in FIGS. 8 through 11, the IC chip 17 of the semiconductor package 15 is thermally connected to the heat receiving portion 26 of the heat sink 24 by way of a heat diffusing member 45. The heat diffusing member 45 has a diffusion plate 46 and a pair of lateral plates 47. The diffusion plate 46 and the lateral plates 47 are typically made of a metal material such as aluminum alloy or copper alloy that is highly thermally conductive. They are also electrically conductive.

The diffusion plate 46 has a size substantially equal to the base substrate 16 of the semiconductor package 15 and a thickness of about 2 mm.

The diffusion plate 46 has a first thermal contact surface 48a and a second thermal contact surface 48b located opposite to the first thermal contact

surface 48a. The first thermal contact surface 48a is located vis-à-vis the semiconductor package 15. The first thermal contact surface 48a has an area far greater than that of the radiation surface 19 of the IC chip 17. The second thermal contact surface 48b is located vis-à-vis the heat receiving portion 26 of the heat sink 24. The second thermal contact surface 48b has an area far greater than that of the radiation surface 19 of the IC chip 17. The first and second thermal contact surfaces 48a, 48b are made very flat and smooth.

The diffusion plate 46 is provided with a pair of recesses 49a, 49b. The recesses 49a, 49b are open to the heat receiving portion 26 and extend respectively along the corresponding opposite edges of the second thermal contact surface 48b.

The lateral plates 47 extend respectively along the corresponding opposite edges of the diffusion plate 46. The lateral plates 47 are provided with respective support parts 52. The support parts 52 are bent perpendicularly so as to be driven into the respective recesses 49a, 49b. The support parts 52 are then rigidly fitted to the respective recesses 49a, 49b by soldering, welding or some other appropriate means.

As best shown in FIGS. 7 and 8, the lateral plates 47 are held by the diffusion plate 46 and stand upright perpendicularly relative to the first and second

thermal contact surfaces 48a, 48b. The lateral plates 47 project upward from the first thermal contact surface 48a by an amount greater than the projection of the IC chip 17 relative to the base substrate 16.

5 Thus, the projecting sections of the lateral plates 47 are located vis-à-vis relative to each other with the first thermal contact surface 48a interposed between them.

Each of the lateral plates 47 is provided at the longitudinal opposite ends thereof with a pair of
10 tongues 53 that are bent inwardly and perpendicularly. Each of the tongues 53 and the corresponding end of the lateral plate 47 cooperate with each other to form an engaging section 54 that is perpendicularly bent.
15 The engaging sections 54 are arranged at the respective four corners of the first thermal contact surface 48a and correspond to the respective four corners 18 of the base substrate 16 of the semiconductor package 15. The corners 18 of the base substrate 16 are engaged
20 respectively with the corresponding engaging sections 54 to define the relative positional relationship between the semiconductor package 15 and the heat diffusing member 45.

Each of the support parts 52 of the lateral plates
25 47 has a pair of spring sections 55 formed by bending the lateral plates 47 obliquely downwardly so that they may be resiliently deformed in the direction of

the height of the diffusion plate 46. The tip ends of the spring sections 55 extend downward below the second thermal contact surface 48b and contact the heat receiving portion 26 of the heat sink 24.

5 With the above described arrangement, the heat diffusion member 45 is constantly urged upward by the spring sections 55 between the heat receiving portion 26 and the semiconductor package 15. As a result, the first thermal contact surface 48a of
10 the diffusion plate 46 is pushed upward toward the radiation surface 19 of the IC chip 17.

 Additionally, the spring sections 55 are held between the heat diffusing member 45 and the heat receiving portion 26 in a compressed state to
15 electrically connect the heat diffusing member 45 and the heat sink 24. Thus, the heat diffusing member 45 is connected to the grounding pads of the circuit substrate 13 by way of the heat sink 24.

 As shown in FIGS. 9 through 11, the heat diffusing
20 member 45 is held in a position biased toward the semiconductor package 15 between the heat receiving portion 26 and the semiconductor package 15. As a result, a gap S1 is produced between the first thermal contact surface 48a of the heat diffusing
25 member 45 and the radiation surface 19 of the IC chip 17, and also another gap S2 is produced between the second thermal contact surface 48b of the heat

diffusing member 45 and the heat receiving portion 26.
The gap S1 is narrower than the gap S2.

5 The gap S1 is held to a value infinitesimally
close to 0 in order to efficiently conduct heat from
the IC chip 17 to the heat diffusing member 45.
A first soft heat conducting member 56 typically made
of grease is arranged in the gap S1. The first heat
conducting member 56 is held in tight contact with the
10 radiation surface 19 of the IC chip 17 and the first
thermal contact surface 48a of the heat diffusing
member 45 to thermally connect the IC chip 17 and the
heat diffusing member 45.

15 The gap S2 is held to a value that can
sufficiently absorb the dimensional variances of the
heat sink 24 and the difference between the designed
height and the actual height of the semiconductor
package 15 relative to the circuit substrate 13.
A second soft heat conducting member 57 typically made
of grease is arranged in the gap S2. The second heat
20 conducting member 57 is held in tight contact with
the second thermal contact surface 48b of the heat
diffusing member 45 and the heat receiving portion 26
to thermally connect the heat diffusing member 45
and the heat sink 24. Therefore, the thickness of
25 the first heat conducting member 56 is smaller than
that of the second heat conducting member 57.

The heat diffusing member 45 shows a thermal

conductivity ($W / (m \cdot K)$) greater than the first and second heat conducting members 56, 57. In other words, the heat diffusing member 45 conducts heat better than the first and second heat conducting members 56, 57.

5 Thus, the heat transmitted from the IC chip 17 to the diffusion plate 46 of the heat diffusing member 45 by way of the first heat conducting member 56 is dispersed along the first and second thermal contact surfaces 48a, 48b so that heat is transmitted to the second heat
10 conducting member 57 from an area greater than the radiation surface 19 of the IC chip 17.

As shown in FIGS. 2 and 3, the heat receiving portion 26 of the heat sink 24 has a heat emitting surface 60. The heat emitting surface 60 is located
15 remotely from the semiconductor package 15 and directed to the bottom wall 5a of the housing 5. The heat emitting surface 60 has a flat area greater than the semiconductor package 15 and is covered by a soft heat conducting sheet 61.

20 As shown in FIGS. 12 and 13, the bottom wall 5a of the housing 5 is provided with an opening 62 located vis-à-vis the heat emitting surface 60 of the heat sink 24. The opening 62 is dimensionally larger than the heat emitting surface 60. The opening 62 is
25 covered by a cover 63. The cover 63 is removably supported by the bottom wall 5a by way of a screw 64.

The cover 63 has a plurality of through holes 65,

which are arranged to form a checker. Therefore, the heat conducting sheet 61 is exposed to the bottom wall 5a of the housing 5 by way of the through holes 65.

5 As shown in FIGS. 1 and 2, the cooling apparatus 2 for cooling the portable computer 1 has an apparatus main body 70. The apparatus main body 70 has a flat box-like profile and corresponds dimensionally to the rear half of the housing 5. The upper surface of the
10 apparatus main body 70 serves as receiving surface 71 for receiving the rear half of the housing 5. The receiving surface 71 is provided with a number of lock claws 73. As the housing 5 is placed on the receiving surface 71, the lock claws 73 releasably catch the
15 bottom wall 5a of the housing 5. Then, the housing 5 is locked to the receiving surface 71.

The apparatus main body 70 contains an auxiliary heat sink 75. The auxiliary heat sink 75 is typically made of a metal material such as aluminum alloy that is
20 thermally highly conductive. The heat sink 75 has a number of heat receiving projections 76 projecting upward from the top surface thereof. The heat receiving projections 76 have a prism-like profile so that they can be inserted respectively into the through
25 holes 65 of the cover 63 and are arranged to form a checker. The heat receiving projections 76 are exposed on the receiving surface 71 of the apparatus

main body 70. Each of the heat receiving projections 76 has a flat contact surface 76a at the tip end thereof. The contact surfaces 76a of the heat receiving projections 76 are flush with each other.

5 Thus, as the housing 5 of the portable computer 1 is placed on the receiving surface 71, the heat receiving projections 76 come to be located respectively right under the corresponding through holes 65 of the cover 63 so that the contact surfaces 10 76a of the heat receiving projections 76 face the heat conducting sheet 61.

 The auxiliary heat sink 75 is supported by the apparatus main body 70 in such a way that it is vertically movable between a first position where the 15 contact surfaces 76a of the heat receiving projections 76 project above the receiving surface 71 and a second position where the contact surfaces 76a of the heat receiving projections 76 are substantially flush with the receiving surface 71. The auxiliary heat sink 75 20 can be moved vertically from the first position to the second position, or vice versa, by means of an operating mechanism 78.

 The procedure for connecting the portable computer 1 to the cooling apparatus 2 for use will now 25 be described.

 Firstly, the housing 5 is placed on the receiving surface 71 of the apparatus main body 70 and securely

10085429.000000

held to the receiving surface 71 by means of the lock claws 73. Under this condition, the operating mechanism 78 is operated to push up the auxiliary heat sink 75 from the second position to the first position.

5 As a result, the contact surfaces 76a of the heat receiving projections 76 are driven into the inside of the housing 5 through the respective through holes 65 of the cover 63 and pushed against the heat conducting sheet 61.

10 Thus, heat conducting sheet 61 is sandwiched by the heat emitting surface 60 of the heat sink 24 and the contact surfaces 76a of the heat receiving projections 76 so that the heat sink 24 is thermally connected to the auxiliary heat sink 75 by way of the
15 heat conducting sheet 61.

At this time, the heat receiving portion 26 having the heat emitting surface 60 is subjected to a force exerted by the heat receiving projections 76 and trying to push it up and move it away from the bottom wall 5a of the housing 5. However, since the heat receiving
20 portion 26 is rigidly secured to the bottom wall 5a of the housing 5 at two positions on the diagonal Z by means of screws 29 and firmly held there, it can reliably resist the force and remain in position.
25 Thus, the heat receiving portion 26 is prevented from becoming rickety and/or being lifted up when the housing 5 is brought into contact with the cooling

10085423.00228002

apparatus 2.

As the portable computer 1 is operated, the IC chip 17 of the semiconductor package 15 generates and emits heat. The heat generated by the IC chip 17 is transmitted to the diffusion plate 46 of the heat diffusing member 45 by way of the first heat conducting member 56 and then to the heat receiving portion 26 of the heat sink 24 by way of the second heat conducting member 57. As a result, the heat emitting surface 60 of the heat receiving portion 26 is heated to a high temperature by the heat transmitted from the IC chip 17. The heat emitting surface 60 is thermally connected to the auxiliary heat sink 75 of the cooling apparatus 2 by way of the heat conducting sheet 61. Thus, the heat transmitted from the IC chip 17 to the heat receiving portion 26 is directly transmitted to the auxiliary heat sink 75.

Consequently, the thermal capacity of the heat transmission path extending from the IC chip 17 to the auxiliary heat sink 75 by way of the heat sink 24 is increased. Therefore, the radiation efficiency of the heat generating IC chip 17 is raised to properly maintain the environmental temperature of the semiconductor package 15 in operation.

If the temperature of the semiconductor package 15 rises above a predetermined level while the portable computer 1 is in operation, the fan unit 25 starts to

10085429.00000000

operate. Then, cooling air is led to the cooling air path 33 of the heat sink 24.

The cooling air from the fan unit 25 forcibly cools the heat exchanging portion 27 of the heat sink 24 as it flows through the cooling air path 33 before it is forced out from the housing 5 through the cooling air outlet port 34. Therefore, the heat transmitted from the heat receiving portion 26 to the heat exchanging portion 27 is partly expelled to the outside of the housing 5 by the flow of cooling air to accelerate the thermal discharge of the semiconductor package 15.

With the above described arrangement, the heat diffusing member 45 is sandwiched between the IC chip 17 and the heat receiving portion 26. The first thermal contact surface 48a of the heat diffusing member 45 is pressed against the radiation surface 19 of the IC chip 17 by the paired spring sections 55. Therefore, the gap S1 between the first thermal contact surface 48a and the radiation surface 19 is held infinitesimally close to 0. In other words, the first heat conducting member 56 arranged in the gap is made very thin. Thus, the thermal resistance of the area thermally connecting the first thermal contact surface 48a and the radiation surface 19 is minimized so that the heat generated by the IC chip 17 can be efficiently transmitted to the diffusion plate 46 of the heat

diffusing member 45.

Additionally, the first and second thermal contact surfaces 48a, 48b of the diffusion plate 46 have a surface area far greater than that of the radiation surface 19 of the IC chip 17, and the diffusion plate 46 shows a thermal conductivity far greater than the first and second heat conducting members 56, 57. Thus, the heat transmitted from the IC chip 17 to the diffusion plate 46 is quickly dispersed to every corner of the diffusion plate 46 along the first and second thermal contact surfaces 48a, 48b. As a result, heat is transmitted from the IC chip 17 to the heat receiving portion 26 by way of the expanded area that is by far larger than its radiation surface 19 and the second heat conducting member 57.

Thus, the thermal contact area of the heat diffusing member 45 and the heat receiving portion 26 is dimensioned so as to satisfactorily meet the required rate of thermal transmission. In other words, the flow rate of heat per unit area is minimized. Therefore, the thermal resistance of the thermal contact area of the heat diffusing member 45 and the heat receiving portion 26 can be held to a sufficiently low level if the gap S2 between the heat diffusing plate 46 and the heat receiving portion 26 is greater than the gap S1 and the second heat conducting member 57 has a significant thickness. Consequently, the

difference between the temperature of the second thermal contact surface 48b and that of the heat receiving portion 26 is minimized.

As described above, heat can be transmitted efficiently from the IC chip 17 to the heat sink 24 to raise the efficiency of thermal discharge of the IC chip 17 by arranging the heat diffusing member 45 in the heat transmission path from the IC chip 17 to the heat sink 24.

Additionally, with the above described arrangement, if the distance between the heat receiving portion 26 and the IC chip 17 departs from the design value due to, for instance, the dimensional variances of the heat sink 24, the soft second heat conducting member 57 contained in the gap S2 is strained and deformed to absorb the change in distance.

More specifically, as the second heat conducting member 57 is strained and deformed, the diffusion plate 46 of the heat diffusing member 45 is apparently held to a floating state relative to the heat sink 24. This means that the heat receiving portion 26 of the heat sink 24 does not need to be arranged in a floating state from the very beginning and hence any movable part can be eliminated from the heat sink 24 to structurally simplify the design of the heat sink 24 and allow the heat sink 24 to have reduced dimensions and light weight.

At the same time, as the heat sink 24 can avoid any movable part, its mechanical strength is improved to make the heat sink 24 free from becoming rickety during transportation of the portable computer 1.

Furthermore, with the above described arrangement, the heat diffusing member 45 laid on the semiconductor package 15 is electrically connected to the grounding layer of the circuit substrate 13 by way of the heat sink 24. Therefore, the semiconductor package 15 can be electromagnetically shielded by utilizing the heat diffusing member 45. Thus, any electromagnetic noise from the semiconductor package 15 can be prevented from leaking, which is greatly advantageous as an anti-noise measure.

While grease is used for the first heat conducting member 56 in the above described first embodiment, the present invention is by no means limited thereto. For instance, solder may be used in place of grease. Since the thermal conductivity of solder is by far greater than that of grease, the thermal resistance of the area thermally connecting the IC chip 17 and the diffusion plate 46 can be reduced further. Then, heat can be transmitted from the IC chip 17 to the diffusion plate 46 highly efficiently.

FIGS. 14A and 14B schematically illustrate a second embodiment of the invention.

The second embodiment differs from the first

1008543.002800

embodiment only in terms of the configuration of the lateral plates 47 of the heat diffusing member 45. Otherwise, the second embodiment is identical to the first embodiment.

5 Each of the lateral plates 47 of the heat diffusing member 45 of this embodiment has extensions 81 extending upward from the upper edges of the respective tongues 53 and each of the extensions 81 is provided with an engaging section 82 formed by inwardly
10 bending an upper end part of the extension 81. The respective engaging sections 82 removably hook on the corresponding other surfaces 16b at the corners 18 of the base substrate 16 of the semiconductor package 15. Thus, the heat diffusing member 45 is held to the
15 semiconductor package 15 at the four corners thereof corresponding to the respective engaging sections 54.

 With the above described arrangement of the second embodiment, the heat diffusing member 45 can be held hooked to the semiconductor package 15 mounted on the
20 circuit substrate 13. Therefore, the heat diffusing member 45 is prevented from dropping or being displaced when it is placed in position between the semiconductor package 15 and the heat sink 24. Thus, the heat
25 diffusing member 45 can be handled with ease to improve the efficiency of the operation of assembling the portable computer 1 and the cooling unit 2 and thermally connecting the semiconductor package 15 and

the heat sink 24.

FIGS. 15 and 16 schematically illustrate a third embodiment of the invention.

5 The third embodiment differs from the first embodiment only in that the effect of shielding the semiconductor package is improved by utilizing the heat diffusing member 45. Otherwise, the third embodiment is identical to the first embodiment.

10 As shown in FIG. 15, a number of grounding pads 91 are arranged on the mount surface 13a of the circuit substrate 13. The pads 91 are arranged so as to surround the component mounting region of the semiconductor package 15. The pads 91 are electrically connected to the grounding layer (not shown) on the
15 inside of the circuit substrate 13.

Each of the lateral plates 47 of the heat diffusing member 45 has terminal sections 92 as integral parts thereof extending upward from the upper edges of the respective tongues 53. The terminal
20 sections 92 are arranged so as to surround the semiconductor package 15 and are soldered respectively to the corresponding pads 91 of the circuit substrate 13. Thus, the heat diffusing member 45 is directly connected to the grounding layer
25 of the circuit substrate 13.

With the above described arrangement of the third embodiment, the heat diffusing member 45 cooperates

with the circuit substrate 13 to sandwich the semiconductor package 15 and is electrically connected to the grounding layer of the circuit substrate 13.

Thus, the heat diffusing member 45 operates as a proximal conductor that is adapted to surround the semiconductor package 15 so that it can be used as a shield for preventing any electromagnetic noise produced by the semiconductor package 15 from leaking out. Therefore, the effect of shielding the semiconductor package 15 can be improved over a wide range from a low frequency zone to a high frequency zone.

Additionally, since the terminal sections 92 of the heat diffusing member 45 are soldered to the circuit substrate 13, the heat diffusing member 45 is rigidly held to the circuit substrate 13. Therefore, the heat diffusing member 45 is prevented from dropping or being displaced when the semiconductor package 15 and the heat sink 24 are thermally connected to each other, improving the efficiency of the operation of assembling the portable computer 1.

FIG. 17 schematically illustrates a fourth embodiment of the invention.

In the fourth embodiment, a number of bosses 101 are integrally formed on the heat receiving portion 26 of the heat sink 24. The bosses 101 project upward respectively toward the corresponding pads 91 of the

circuit substrate 13. The tip facet 101a of each of the bosses 101 is placed vis-à-vis the corresponding one of the pads 91. The terminal sections 92 of the heat diffusing member 45 are arranged respectively
5 between the tip facets 101a of the bosses 101 and the pads 91.

The circuit substrate 13 is rigidly secured to the bosses 101 by means of screws 102. As a result of this securing arrangement, the terminal sections 92 of the
10 heat diffusing member 45 are pinched respectively between the front facets 101a of the bosses 101 and the corresponding pads 91 and directly connected to the grounding layer of the circuit substrate 13.

With the above described arrangement of the fourth
15 embodiment, the heat diffusing member 45 cooperates with the circuit substrate 13 to sandwich the semiconductor package 15 and is electrically connected to the grounding layer of the circuit substrate 13 as in the case of the third embodiment. Thus, the heat
20 diffusing member 45 operates more reliably as a proximal conductor adapted to surround the semiconductor package 15 so that it can be used as a shield for preventing any electromagnetic noise produced by the semiconductor package 15 from
25 leaking out.

Additionally, the heat diffusing member 45 is rigidly held to the circuit substrate 13 by way of

the terminal sections 92. Therefore, the heat
diffusing member 45 is prevented from dropping or being
displaced when the semiconductor package 15 and the
heat sink 24 are thermally connected to each other,
5 improving the efficiency of the operation of assembling
the portable computer 1.

FIG. 18 schematically illustrates a fifth
embodiment of the invention.

In the fifth embodiment, a bulking agent 110 is
10 used fill the gap between the first thermal contact
surface 48a of the heat diffusing member 46 and the
base substrate 16 of the semiconductor package 15.
The bulking agent 110 may typically be a thermoplastic
resin material having an adhesive property such as
15 a paraffin-type material. The bulking agent 101 bonds
and securely holds the heat diffusing member 45 and the
semiconductor package 15 together so as to make them
surround the heat generating IC chip 17.

With the above described arrangement of the fifth
20 embodiment, since the heat diffusing member 45 is
rigidly secured to the semiconductor package 15 by
means of the bulking agent 110, the positional
relationship of the semiconductor package 15 and
the heat diffusing member 45 is stably maintained.
25 Therefore, the heat diffusing member 45 is prevented
from dropping or being displaced when the semiconductor
package 15 and the heat sink 24 are thermally connected

to each other, improving the efficiency of the operation of assembling the portable computer 1.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, 5 the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as 10 defined by the appended claims and their equivalents.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25